

**Listing of Claims:**

1. (Currently Amended) A portable communication terminal comprising:

a display;

image storage means for storing items of image data;

5 address book data storage means for storing at least one item of contact address information and additional information associated with the item of contact address information, by establishing a link therebetween,

link storage means for storing a link between at least one 10 item of contact address information in the address book data storage means and a storage address of a corresponding item of image data stored in the image storage means;

communication log storage means for storing a plurality of communication logs, including a communication log comprising a 15 plurality of items of contact address information corresponding to data transmitted by the portable communication terminal and a communication log comprising a plurality of items of contact address information corresponding to data received by the portable communication terminal;

20 means for selecting issuing an instruction to display a selected one of the communication logs to be displayed on the display;

means for displaying, when the instruction is issued to display one of the communication logs, in a list on the display  
25 the plurality of items of contact address information of the selected communication log and a display region for issuing an instruction to display at least one image with the displayed communication log;

means for, instructing when an operation of a key associated with the display region for issuing the instruction to display the at least one image with the displayed communication log is detected, issuing an instruction to display the displayed communication log on the display together with images the at least one image;

means for referring to the link storage means to determine whether any item of image data is linked to any of the items of contact address information displayed on the display in the displayed communication log, when images are instructed to be displayed the instruction is issued to display the at least one image together with the displayed communication log; and

means for, when it is determined that at least one item of image data is linked to a corresponding one of the displayed items of contact address information, reading out and resizing the at least one item of image data and displaying the at least one read out and resized item of image data [[,]] together with

the corresponding item of contact address information in the displayed communication log; and, in the list on the display.

50       means for, when the displayed communication log is displayed together with the at least one read out and resized item of image data, and when an operation of the key is detected, issuing an instruction to return to displaying the displayed communication log without displaying any item of image data linked to any of the items of contact address information in the displayed communication log.

2. (Previously Presented) A terminal according to claim 1, further comprising means for determining whether or not information identical to any of the items of contact address information stored in the communication log storage means is present in the address book data storage means, and, if it is determined that at least one of the items of contact address information in the selected communication log is present in the address book data storage means, the display is controlled to display the additional information associated with the at least one item of contact address information when displaying the selected communication log.

10       3. (Currently Amended) A terminal according to claim 1, further comprising:

means for selecting one of the items of contact address information from the contact address information displayed on the display in the list in the displayed communication log; and

5 means for causing the display to display information with respect to past communication corresponding to the selected item of contact address information.

4. (Previously Presented) A terminal according to claim 2, further comprising:

means for selecting desired additional information from the additional information displayed on the display; and

5 means for causing the display to display the selected additional information and information with respect to past communication.

5. (Previously Presented) A terminal according to claim 4, wherein the additional information includes a plurality of pieces of contact address information, and the plurality of pieces of contact address information and an icon indicating attributes thereof are displayed when the additional information is selected.

6. (Previously Presented) A terminal according to claim 3, further comprising:

means for determining whether or not a list display instruction is issued after one of the items of contact address information is selected; and

5 means for, when the list display instruction is issued, (i) causing the selected communication log to be displayed in a list one of (i) without the images, if the images were not displayed when the one of the items of contact address

10 information was selected, and (ii) with the images, if the images were displayed when the one of the items of contact address information was selected.

7. (Previously Presented) A terminal according to claim 4, further comprising:

means for determining whether or not an image data display instruction is issued after the desired additional information is selected; and

5 means for, when the image data display instruction is issued, (i) reading out image data, from the image storage means, that corresponds to the item of contact address information corresponding to the selected additional information, based on a

10 storage address of the image data linked to the item of contact address information by a link stored by the link storage means, (ii) resizing the image data, and (iii) displaying the resized

image data on the display means in place of the selected additional information.

8. (Currently Amended) A terminal according to claim 1, wherein the communication logs comprise an outgoing call log and an incoming call log, and the means for selecting one of the communication logs comprises:

5       means for instructing to display the outgoing call log;  
          means for instructing to display the incoming call log; and  
          means for switching between displaying the outgoing call log  
and the incoming call log in accordance with the  
respective instructions.

9. (Currently Amended) A terminal according to claim 1, further comprising means for always displaying a reception state of ~~the~~ a radio signal on the display.

10. (Currently Amended) A terminal according to claim 7, wherein the resized and displayed image data, which is displayed in response to the image display instruction, comprises moving image data.

11. (Previously Presented) A terminal according to claim 1, further comprising:

image capturing means for capturing image data; and  
storage control means for causing the image storage means to  
5 store image data captured by the image capturing means.

12. (Currently Amended) An image display method for a portable communication terminal including a display section, an image memory which stores image data, and an address book data memory, said method comprising:

5 storing, in a link memory, a link between at least one item of data in the address book data memory and a storage address of a corresponding item of image data stored in the image memory;

storing, in a communication log memory, communication logs including a communication log comprising a plurality of items  
10 of contact address information corresponding to data transmitted by the portable communication terminal and a communication log comprising a plurality of items of contact address information corresponding to data received by the portable communication terminal;

15 selecting issuing an instruction to display a selected one of the communication logs stored in the communication log memory to be displayed on the display section;

displaying, when the instruction is issued to display one of the communication logs, in a list the plurality of items  
20 of contact address information of the selected communication log

and a display region for issuing an instruction to display at least one image with the displayed communication log;

detecting an operation of a key associated with the display region for issuing the instruction to display the at least one image with the displayed communication log is detected;

25       instructing issuing, when the operation of the key is detected, an instruction to display the displayed communication log on the display section together with ~~images~~ the at least one image;

30       referring to the link memory to determine whether any item of image data is linked to any of the items of contact address information displayed on the display section in the displayed communication log, when ~~images are instructed to be displayed the instruction is issued to display the at least one image~~ together with the displayed communication log; and

35       when it is determined that at least one item of image data is linked to a corresponding one of the displayed items of contact address information, reading out and resizing the at least one item of image data and displaying the read out and

40       resized image data [[,]] together with the corresponding item of contact address information in the displayed communication log; and, in the list on the display section.

when the displayed communication log is displayed together with the at least one read out and resized item of image data,

45       and when an operation of the key is detected, issuing an instruction to return to displaying the displayed communication log without displaying any item of image data linked to any of the items of contact address information in the displayed communication log.

13. (Previously Presented) A method according to claim 12, further comprising determining whether or not information identical to any of the items of contact address information stored in the communication log memory is present in the address book data memory, and, if it is determined that at least one of the items of contact address information in the selected communication log is present in the address book data memory, displaying additional information associated with the at least one item of contact address information when the selected communication log is displayed.

10       14. (Currently Amended) A method according to claim 12, further comprising:

5       selecting one of the items of contact address information from the contact address information ~~displayed on the display section in the list in the displayed communication log;~~ and

causing the display section to display information with respect to past communication corresponding to the selected item of contact address information.

15. (Previously Presented) A method according to claim 13, further comprising:

selecting desired additional information from the additional information displayed on the display section; and

5 causing the display section to display the selected additional information and information with respect to past communication.

16. (Previously Presented) A method according to claim 15, wherein the additional information includes a plurality of pieces of contact address information, and the plurality of pieces of contact address information and attributes thereof are displayed 5 when the additional information is selected.

17. (Previously Presented) A method according to claim 14, further comprising:

determining, after one of the items of contact address information is selected, whether or not a list display 5 instruction is issued; and

when a list display instruction is issued, displaying the selected communication log in a list one of (i) without the images, if the images were not displayed when the one of the items of contact address information was selected, and (ii) with 10 the images, if the images were displayed when the one of the items of contact address information was selected.

18. (Previously Presented) A method according to claim 15, further comprising:

determining, after the desired additional information is selected, whether or not an image data display instruction is issued; and

when the image data display instruction is issued,  
(i) reading out image data, from the image memory, that corresponds to the item of contact address information corresponding to the selected additional information, based on a storage address of image data linked to the item of contact address information by a link stored in the link memory,  
(ii) resizing the image data, and (iii) displaying the resized image data on the display section in place of the selected additional information.

19. (Currently Amended) A method according to claim 18, wherein the resized and displayed image data, which is displayed

in response to the image display instruction, comprises moving image data.

20. (Previously Presented) A method according to claim 12, wherein the portable communication terminal further comprises an image capturing section, and the method further comprises storing image data captured by the image capturing section in the 5 image memory.